

HF109

1" - 60 W - 108 dB - 16 Ohm



NOMINAL SPECIFICATIONS

Throat Diameter	25,4 mm (1 in)
Overall Diameter	121 mm (4.76 in)
180° Mounting Holes Diameter (2xM6)	76 mm (2.99 in)
Depth	55 mm (2.17 in)
Net Weight	2.2 kg (4.9 lb)
Shipping Box (Single carton box)	185 x 170 x 102 mm (7.3 x 6.7 x 4.0 in)
Shipping Weight	2.5 kg (5.5 lb)

PART NUMBER

Faston Terminals - 16 Ohm Version	00444203
-----------------------------------	----------

NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) 12 dB/oct or higher slope high-pass filter
- (4) Averaged within the frequency range
- (5) The phase plug is recessed from the driver's exit which is at the end of a conical adaptation horn.

TECHNICAL PARAMETERS

Nominal Impedance	16 Ohm
Minimum Impedance	13.2 Ohm
AES Power Handling (1)	60 W
Maximum Power Handling (2)	120 W
Minimum Crossover Frequency (3)	1.3 kHz
Sensitivity (1W/1m) (4)	108 dB
Frequency Range	1-20 kHz
Voice Coil Diameter	44 mm (1.73 in)
Winding Material	Al
Former Material	Kapton
Diaphragm Material	Ketone Polymer
Diaphragm Shape	Dome
Winding Depth	2.9 mm (0.11 in)
Magnetic Gap Depth	2.85 mm (0.11 in)
Flux Density	1.8 T
Magnet	Ferrite Ring
Re	10.5 Ohm
Phase Plug Design	Annular
Exit Angle (5)	13° Conical
NET Air Volume filled by HF Driver	0.43 dm ³ (0.015 ft ³)

